

Shingle Applicator Guide

certainteed shingle applicator™s manual presidential ... - 142 chapter 15 certainteed shingle applicator™s manual alignment and shiplap notches to maintain the correct 5" and 15" diagonal offset pattern, use the alignment notches at 5 1/2" and 15 1/2" from the right edge of the shingle. these notches are pre-cut into the top of each shingle and serve

your objective - certainteed - 128 chapter 15 certainteed shingle applicator™s manual alignment and shiplap notches to maintain the correct 5" and 15" diagonal offset pattern, use the alignment notches at 5 1/2" and 15 1/2" from the right edge of the shingle. these notches are pre-cut into the top of each shingle and serve

polymeric slate tile roof system - sustainable steep-slope ... - installation steps ecostar makes every effort to maintain the quality and consistency of all products, however, shade variations will occur within all tile products.

exterior finishes - cra | california redwood association - general finishing tips apply finishes on windless days. temperature should be between 50 and 70 degrees fahrenheit. surfaces should be clean and dry new structures built with unseasoned wood should air-dry one month before finishing. back-priming is recommended for all exterior finishes, particularly paints.

Related PDFs :

[Abc Def](#)

[Sitemap](#) | [Best Seller](#) | [Home](#) | [Random](#) | [Popular](#) | [Top](#)